



Notes:

1. Type: Film to Glass
2. Operating Voltage: ≤10V
3. Operation Temperature: 20℃~65℃
- Storage Temperature: -30℃~70℃
4. Life Time: 1,000,000 times
5. Connect Material: FPC
6. Response Time: ≤10ms
7. Linearity: ≤1.5%
8. Transmittance: ≥75%
9. Surface Hardness: ≥3H (pencil)
10. Operation force: 60g~150g
11. Resistance: X: 433Ω-1059Ω Y: 168Ω-411Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES

>200MM	±2.0MM
1600-X <200MM	±1.20MM
1200-X <1600MM	±0.80MM
800-X <1200MM	±0.50MM
400-X <800MM	±0.40MM
120-X <400MM	±0.20MM
30-X <120MM	±0.10MM

		GreenTouch Technology Co., Ltd	
Model No.:	GT-19-188-1	Size:	19"
Structure:	GF	Unit:	mm
Design:	398	Date:	2015.10.5
Check:	417741	Date:	2015.10.5
Revision:	E28	Date:	2015.10.5
Scale:	1:1	Ratio:	1:1
Page:	1/1	Version:	2.0