



- Notes:
- 1.Type: Film to Glass
 - 2.Operating Voltage: 510V
 - 3.Operating Temperature: -20°C ~ 65°C
 - 4.Life Time: 1,000,000 times
 - 5.Connect Material: FPC
 - 6.Response Time: 10ms
 - 7.Luminance: 15%
 - 8.Transmittance: > 75%
 - 9.Surface Hardness: 3H (pencil)
 - 10.Operation force: 60g ~ 150g

11. Resistances: 50Ω < PIN1, PIN2 < 250Ω
50Ω < PIN2, PIN4 < 250Ω
50Ω < PIN5, PIN1 < 250Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES 40.5%

1600 X 5200MM	±1.50MM
1200 X 5120MM	±0.50MM
800 X 5120MM	±0.50MM
400 X 500MM	±0.50MM
300 X 5120MM	±0.50MM
< 30MM	±0.10MM

Model No.		GT-SM-19A-1		Size		19"		Ratio		4:3	
Structure		GTF		Unit		mm		Scale		1:1	
Design		9/26		Date		2018/01/28		Page		1/1	
Check		4/17/18		Date		2018/01/28		Version		A0	
Released		E2K		Date		2018/01/28					

GreenTouch Technology Co., Ltd