



由 Autodesk 教育版产品制作

由 Autodesk 教育版产品制作

- Notes:
1. Type: Film to Glass
  2. Operating Voltage:  $\leq 10V$
  3. Operation Temperature:  $20^{\circ}C \sim 65^{\circ}C$   
Storage Temperature:  $-30^{\circ}C \sim 70^{\circ}C$
  4. Life Time: 1,000,000 times
  5. Connect Material: FPC
  6. Response Time:  $\leq 10ms$
  7. Linearity:  $\leq 1.5\%$
  8. Transmittance:  $\geq 75\%$
  9. Surface Hardness:  $\geq 3H$  (pencil)
  10. Operation force:  $60g \sim 150g$
  11. Resistance: X:  $417\Omega \sim 1152\Omega$  Y:  $155\Omega \sim 378\Omega$

TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS ANGLES: ±0.5%

>200MM	±2.0MM
1600-X < 800MM	±1.20MM
1200-X < 1600MM	±0.80MM
800-X < 1200MM	±0.50MM
400-X < 800MM	±0.30MM
120-X < 400MM	±0.20MM
30-X < 120MM	±0.10MM

<b>绿触科技</b>		<b>GreenTouch Technology Co., Ltd</b>	
Model No.:	GT-4W-18.5A-1	Size:	18.5"
Structure:	GHF	Unit:	mm
Design:	李洪	Date:	2015.5.5
Check:	付作东	Date:	2015.5.5
Reviewed:	张强	Date:	2015.5.5
Ratio:	1:1	Scale:	1:1
Page:	1/1	Version:	A0