



- Notes:
1. Type: Film to Glass
 2. Operating Voltage: ≤ 10V
 3. Operation Temperature: -20°C ~ 65°C
Storage Temperature: -30°C ~ 70°C
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: ≤ 10ms
 7. Linearity: ≤ 1.5%
 8. Transmittance: ≥ 75%
 9. Surface Hardness: ≥ 3H (pencil)
 10. Operation force: 60g ~ 150g
 11. Resistance: X: 360Ω-880Ω Y: 203Ω-495Ω

TOLERANCES (UNLESS OTHERWISE STATED)
DECIMALS ANGLES ±0.25%

1600< X < 2500MM	±1.20MM
1200< X < 1600MM	±1.20MM
800< X < 1200MM	±0.50MM
400< X < 800MM	±0.50MM
120< X < 400MM	±0.50MM
30< X < 120MM	±0.10MM

		GreenTouch Technology Co., Ltd	
Model No.:	GT-4H-12.1-1	Size	12.1"
Structure	G+T	Unit	mm
Design	李松	Date	2015.5
Check	44141	Date	2015.5
Released	2218	Date	2015.5
Scale	1:1	Ratio	4:3
Page	1/1	Version	4.0