



- Notes:
1. Type: Film to Glass
  2. Operating Voltage: 5.10V
  3. Operating Temperature: 20°C ~ 65°C
  4. Life Time: 1,000,000 times
  5. Storage Temperature: -30°C ~ 70°C
  6. Connect Material: FPC
  7. Response Time: 5.10ms
  8. Transparency: > 75%
  9. Surface Hardness: 3H (penical)
  10. Operation Force: 90g ~ 150g

11. Resistance: 50Ω < PIN1, PIN2 < 250Ω  
 50Ω < PIN2, PIN4 < 250Ω  
 50Ω < PIN4, PIN5 < 250Ω  
 50Ω < PIN5, PIN1 < 250Ω

TOLERANCES (UNLESS OTHERWISE STATED) DIMENSIONS ANGLES	DECIMALS	FRACTIONS
> 200MM	± 0.25MM	± 0.10MM
1600~ X 5120MM	± 1.50MM	± 0.60MM
1200~ X 5160MM	± 2.00MM	± 0.80MM
800~ X 5120MM	± 0.50MM	± 0.20MM
400~ X 500MM	± 0.50MM	± 0.20MM
120~ X 540MM	± 0.20MM	± 0.10MM
30~ X 512MM	± 0.10MM	± 0.05MM

GreenTouch		GreenTouch Technology Co., Ltd	
Model No.:	GT-MV-17A-1	Size:	17"
Structure:	GT	Unit:	mm
Design:	41775	Date:	2015.11.11
Check:	41775	Scale:	1:1
Review:	41775	Page:	1/1
		Version:	00