



由 Autodesk 教育版产品制作

- Notes:
1. Type: Film to Glass
 2. Operating Voltage: ≤10V
 3. Operation Temperature: 20℃~65℃
Storage Temperature: -30℃~70℃
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: ≤10ms
 7. Linearity: ≤1.5%
 8. Transmittance: ≥75%
 9. Surface Hardness: ≥3H (pencil)
 10. Operation force: 60g~150g
 11. Resistance: X: 333Ω-814Ω Y: 220Ω-536Ω

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES: ±0.5%

1600< X < 2000MM	±1.20MM
>2000MM	±2.00MM
1200< X < 1600MM	±0.80MM
800< X < 1200MM	±0.50MM
400< X < 800MM	±0.40MM
120< X < 400MM	±0.20MM
30< X < 120MM	±0.10MM
<30MM	±0.10MM

绿触科技		GreenTouch Technology Co., Ltd	
Model No.:	GT-4W-17A-1	Size:	17"™
Structure:	GT-F	Unit:	mm
Design:	4/17/16	Date:	2015.6.5
Check:	4/17/16	Date:	2015.6.5
Revision:	ES5	Date:	2015.6.5
Ratio:		Scale:	1:1
		Page:	1/1
		Version:	A0