



由 Autodesk 教育版产品制作

- Notes:
1. Type: Film to Glass
 2. Operating Voltage: $\leq 10V$
 3. Operation Temperature: $20^\circ C \sim 65^\circ C$
Storage Temperature: $-30^\circ C \sim 70^\circ C$
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: $\leq 10ms$
 7. Linearity: $\leq 1.5\%$
 8. Transmittance: $\geq 75\%$
 9. Surface Hardness: $\geq 3H$ (pencil)
 10. Operation force: $60g \sim 150g$
 11. Resistance: X: $360\Omega - 880\Omega$ Y: $200\Omega - 500\Omega$

TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES: $\pm 0.25^\circ$

$>200MM$	$\pm 2.0MM$
$1600 < X < 200MM$	$\pm 1.20MM$
$1200 < X < 1600MM$	$\pm 0.80MM$
$800 < X < 1200MM$	$\pm 0.50MM$
$400 < X < 800MM$	$\pm 0.40MM$
$120 < X < 400MM$	$\pm 0.20MM$
$50 < X < 120MM$	$\pm 0.10MM$

		GreenTouch Technology Co., Ltd	
Model No.:	GT-4W-15A-1	Size	15"
Structure	GF	Unit	mm
Design	2015.7.5	Date	2015.7.5
Check	2015.7.5	Page	1/1
Revision	2015.7.5	Version	2.0