



- Notes:
- 1.Type: Film to Glass
  - 2.Operating Voltage:  $\leq 10V$
  - 3.Operating Temperature:  $20^{\circ}C \sim 65^{\circ}C$
  - 4.Life Time: 1,000,000 times
  - 5.Connect Material: FPC
  - 6.Response Time:  $\leq 10ms$
  - 7.Linearity:  $\leq 1.5\%$
  - 8.Transmittance:  $\geq 75\%$
  - 9.Surface Hardness:  $\geq 3H$ (pencil)
  - 10.Operation force:  $60g \sim 150g$

11. Resistance:  $50\Omega < PIN1, PIN2 < 250\Omega$   
 $50\Omega < PIN2, PIN4 < 250\Omega$   
 $50\Omega < PIN4, PIN5 < 250\Omega$   
 $50\Omega < PIN5, PIN1 < 250\Omega$

TOLERANCES  
(UNLESS OTHERWISE STATED)  
DECIMALS, ANGLES:  $\pm 0.05^{\circ}$

>200MM	$\pm 1.20MM$
100 - X < 200MM	$\pm 1.20MM$
50 - X < 100MM	$\pm 0.80MM$
20 - X < 50MM	$\pm 0.40MM$
30 - X < 120MM	$\pm 0.20MM$
< 30MM	$\pm 0.10MM$

		GreenTouch Technology Co., Ltd	
Model No.:	GT-SV-22A-1	Size	22" II
Structure	GT-F	Unit	mm
Design	#16	Date	2016.2.25
Check	#17-18	Date	2016.2.25
Release	EEB	Date	2016.2.25
Scale	1:1	Version	A0

