



- Note:**
1. Typical Film to Glass
 2. Operating Voltage: $\leq 10V$
 3. Operating Temperature: $-30^{\circ}C \sim 80^{\circ}C$
 4. Storage Temperature: $-30^{\circ}C \sim 70^{\circ}C$
 5. Storage Time: 1,000,000 hours
 6. ESD Protected: Human Body ESD
 7. Response Time: $\leq 10ms$
 8. Transparency: $\geq 92\%$
 9. Surface Hardness: $\geq 3H$
 10. Operation Force: $\sim 150g$

- 11. Panel Dimensions:**
- MON < PIN1, PIN2 < 2300
 - MON < PIN2, PIN1 < 2300
 - MON < PIN4, PIN3 < 2300
 - MON < PIN5, PIN4 < 2300

TOLERANCES

QUANTITY	ANGLE	DRILL DIA.	POSITION
1-10	±0.1	±0.05	±0.1
11-50	±0.1	±0.05	±0.1
51-100	±0.1	±0.05	±0.1
101-500	±0.1	±0.05	±0.1
501-1000	±0.1	±0.05	±0.1
1000+	±0.1	±0.05	±0.1

格威触控 GreenTouch Technology Co., Ltd

Model No.	GT-10.4-001	Size	10.4"	Resolution	4096
Color	White	Material	MON	Response Time	10ms
Weight	~1.5kg	Operating Voltage	≤10V	Operating Temp.	-30~80°C
Storage Temp.	-30~70°C	Storage Time	1,000,000 hrs	ESD Protection	Human Body ESD
Transparency	≥92%	Surface Hardness	≥3H	Operation Force	~150g