



- Notes:
1. Type: Film to Glass
 2. Operating Voltage: ≤ 10V
 3. Operation Temperature: -20°C ~ 65°C
Storage Temperature: -30°C ~ 70°C
 4. Life Time: 1,000,000 times
 5. Connect Material: FPC
 6. Response Time: ≤ 10ms
 7. Linearity: ≤ 1.5%
 8. Transmittance: ≥ 75%
 9. Surface Hardness: ≥ 3H (pencil)
 10. Operation force: 60g ~ 150g
 11. Resistance: X: 480-1174Ω Y: 1520-3710Ω

TOLERANCES
(UNLESS OTHERWISE STATED)

DECIMALS	ANGLES	±0.5%
>200MM	±2.0MM	
100-200MM	±1.2MM	
75-100MM	±0.8MM	
50-75MM	±0.5MM	
25-50MM	±0.3MM	
12-25MM	±0.2MM	
3-12MM	±0.1MM	

		Green Touch Technology Co., Ltd	
Model No.:	GT-4H-1804-1	Size:	15.6"
Structure:	GTFC	Unit:	mm
Design:	李强	Date:	2015.7.15
Check:	符作秀	Date:	2015.7.15
Released:	符作秀	Date:	2015.7.15
Ratio:	16:9	Scale:	1:1
Version:	A0	Page:	1/1